

[illegible]

[illegible]

[illegible]

| MT-1 and MT-2 Stock Geometry |      |      |      |      |
|------------------------------|------|------|------|------|
| Size                         | S    | M    | L    | XL   |
| HT angle                     | 67   | 67   | 67   | 67   |
| ST angle (Actual)            | 73   | 73.5 | 74   | 74.5 |
| ST Angle (Effective)         | 74.7 | 75.1 | 75.5 | 75.9 |
| ST length (C-T)              | 410  | 440  | 470  | 490  |
| TT length (eff)              | 593  | 621  | 638  | 663  |
| HT length                    | 95   | 105  | 115  | 135  |
| Wheelbase                    | 1135 | 1170 | 1194 | 1226 |
| Chainstay length             | 445  | 445  | 445  | 445  |
| Fork Offset (Recommended)    | 44   | 44   | 44   | 44   |
| Fork Travel (Recommended)    | 120  | 120  | 120  | 120  |
| trail                        | 113  | 113  | 113  | 113  |
| standover                    | 799  | 820  | 840  | 858  |
| BB drop                      | 60   | 60   | 60   | 60   |
| BB height                    | 318  | 318  | 318  | 318  |
| TT angle                     | 23.2 | 20.2 | 17.6 | 16.3 |
| stack                        | 607  | 616  | 626  | 644  |
| reach                        | 420  | 450  | 470  | 495  |
| TT diameter                  | 34.9 | 34.9 | 38.1 | 38.1 |
| ST diameter                  | 34.9 | 34.9 | 34.9 | 34.9 |
| DT diameter                  | 42   | 42   | 44   | 44   |
| SS diameter                  | 19   | 19   | 19   | 19   |

[illegible]

[illegible]

[illegible]

| R Series Caliper Geometry |       |       |       |       |       |       |        |        |        |
|---------------------------|-------|-------|-------|-------|-------|-------|--------|--------|--------|
| Size                      | 48    | 50    | 52    | 54    | 55    | 56    | 58     | 60     | 62     |
| HT angle                  | 71    | 71    | 72.5  | 72.5  | 72.5  | 73    | 73     | 73     | 73     |
| ST angle                  | 74.5  | 74    | 74    | 73.5  | 73    | 73    | 73     | 72.5   | 72     |
| ST length (C-T)           | 480   | 500   | 520   | 540   | 550   | 560   | 580    | 600    | 620    |
| TT length (eff)           | 515   | 525   | 535   | 545   | 555   | 565   | 580    | 595    | 605    |
| HT length                 | 105   | 120   | 130   | 145   | 155   | 165   | 175    | 190    | 210    |
| Wheelbase                 | 976.8 | 983.1 | 976.5 | 982   | 987.1 | 992.5 | 1009.6 | 1019.1 | 1026.4 |
| Chainstay length          | 408   | 408   | 410   | 410   | 410   | 410   | 412    | 412    | 415    |
| fork offset               | 50    | 50    | 43    | 43    | 43    | 43    | 43     | 43     | 43     |
| trail                     | 63.5  | 63.5  | 61.5  | 61.5  | 61.5  | 58.4  | 58.4   | 58.4   | 58.4   |
| standover                 | 734.7 | 750.9 | 771   | 787.2 | 796.1 | 806.7 | 821    | 837.1  | 855.5  |
| BB drop                   | 72    | 72    | 70    | 70    | 70    | 70    | 70     | 70     | 70     |
| BB height                 | 270   | 270   | 268   | 268   | 268   | 268   | 268    | 268    | 268    |
| TT angle                  | 6.5   | 5.8   | 5.4   | 4.8   | 4.8   | 4.9   | 3.7    | 3.3    | 3.4    |
| stack                     | 512   | 526   | 542   | 557   | 566   | 577   | 587    | 601    | 620.2  |
| reach                     | 371   | 372   | 379   | 380   | 382   | 389   | 401    | 406    | 404    |